

## ABSTRACT OF DISCLOSURE

Sub B34  
 In a dynamo electric machine provided with a stator and a permanent magnet type rotor 2, on or near  
 5 circumferential surface of the rotor 2 facing the stator 1 p·n pieces of permanent magnet blocks 21 are disposed, herein p is number of poles of the rotor and n is an integer equal to or more than 2, and each of the permanent magnet blocks satisfies the following  
 10 condition (1);

$$(\theta_i) - (\theta_{i+1}) = (A_i \cdot p / 2) \quad \dots (1)$$

Wherein, when assuming that clockwise direction is plus,  $A_i$  is an angle formed between radial center lines of  $i$ th permanent magnet block and  $(i+1)$ th  
 15 permanent magnet block,  $\theta_i$  is an angle formed between magnetization direction of the  $i$ th permanent magnet block and the outward radial direction thereof, and  $\theta_{i+1}$  is an angle formed between magnetization direction of the  $(i+1)$ th permanent magnet block and  
 20 the outward radial direction thereof, and further, when assuming that stator 1 includes m pieces of salient poles disposed with an equal interval the dynamo electric machine satisfies the following condition (2);

25  $m/p \leq 1.5 \quad \dots (2),$

Sub B35  
 thereby, a permanent magnet type dynamo electric machine with reduced size, increased efficiency and

10066735-020602

decreased cogging torque can be realized.

10066735.020602